



Declaration of performance

Nr 21/250/KA/2021

1. Unique identification code of the product-type:	KNAUF Therm ETIXX Fasada λ 31 d _N 250 (TYP EPS S) EPS -EN 13163-T(2)-L(2)-W(2)-S(5)-P(5)-BS100-DS(N)5-DS(70,-)2-TR100
2. Intended use or uses:	Thermal insulation for buildings
3. Name, registered trade name or registered trade mark and contact address of the manufacturer:	Knauf Industries Polska Sp. z o.o. Adamowice ul. Styropianowa 1, 96-320 Mszczonów
4. Name and contract address of the authorized representative	Not relevant
5. System or systems of assessment and verification of constancy of performance of the construction product	System 3
6a. Harmonized standard:	EN 13163:2012+A1:2015.
Notified testing facility:	Building Research Institute Notified testing laboratory 1488 Polish Centre for Testing and Certification – Notification Number 1434
6b. European Assessment Document	Not relevant
European Technical Assessment	Not relevant
Technical assessment facility:	Not relevant
Notified testing facility	Not relevant

7. Declared performance:			
Essential Characteristics	Performance properties	Declared class/level/NDP ^{a)}	Harmonised technical specification
Thermal resistance	Thermal conductivity and resistance	$R_D - 7,80 \text{ m}^2\text{K/W}$ $\lambda_D - 0,031 \text{ W/mK}$	EN 13163:2012+A1:2015
	Thickness	$T(2)$ $d_N - 250 \text{ [mm]}$	
Reaction to fire	Reaction to fire	E	
Durability of reaction to fire - in function of heat, atmospheric conditions, aging/degradation	Properties Durability ^{b)}	E	
Durability of thermal resistance and thermal conductivity against aging/degradation	Thermal resistance and thermal conductivity ^{c)}	$R_D - 7,80 \text{ m}^2\text{K/W}$ $\lambda_D - 0,031 \text{ W/mK}$	
	Properties Durability	NPD	
Compressive strength	Compressive strength at 10% deformation CS (10) [kPa]	NPD	
Tensile/Flexural strength	Bending strength BS [kPa]	BS 100	
	Tensile strength perpendicular to faces TR [kPa]	TR 100	
Durability of compressive strength against aging and degradation	Compressive creep CC [%]	NPD	
	Freeze-thaw resistance [%]	NPD	
	Long-term thickness reduction [mm]	NPD	
Water permability	Water permeability WL(T)	NPD	
	Water absorbtion WD(V)	NPD	
Vapor permability	Vapor permability [μ]	NPD	
Impact noise transmission index	Dynamic stiffness SD [MN/m ³]	NPD	
	Thickness d ₁ [mm]	NPD	
	Compressibility CP [mm]	NPD	
Continuous glowing combustion	Continuous glowing combustion ^{d)}	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances to the indoor environment ^{d)}	NPD	

^{a)} **NPD** - No Performance declare;
^{b)} No change in reaction to fire properties for EPS products;
^{c)} Thermal resistance and thermal conductivity of EPS products don't change with time;
^{d)} Europe research is ongoing;

8. Appropriate Technical Documentation or Specific Technical Documentation:

Not applicable

The performance of the product identified above is consistent with the set of declared performance.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer:

(name:)

Paweł Zemlik

(place:)

Adamowice

(date:)

06.07.2020

(signature:)

